

# Fast Tracking using GenFit and PHG4Hit

Jin Huang(BNL), Haiwang Yu (NMSU)

Aug. 9, 2016

# Fast tracking with Kalman Filter + pseudo pattern recognition

## Motivation:

- Developed for fsPHENIX. Quickly produce tracking performance with Geant simulation + Kalman Filter. Could be a complete tracking code with real pattern recognition component.
- Jin suggest to generalize this to any detector setups.

## Procedure:

- Simulation
  - $\Rightarrow$  PHG4TruthInfoContainer.
  - $\Rightarrow$  PHG4Hit.
  - $\Rightarrow$  TGeo detector geometry in DST run node (PHGeometry by Jin)
- Feed the Kalman Filter:
  - PHG4Hit  $\Rightarrow$  Measurements: Smear PHG4Hit according to given detector resolution.
  - **Measurements grouping: use MC truth information, "pseudo pattern recognition"**
  - Seed: Smeared MC truth information



# Implementation

New version of *SvtxTrack*: *SvtxTrack\_FastSim*. add two methods to *SvtxTrack*. Need this to do evaluation for multi-track events. Making the complete Track->Cluster->Cell->PHG4Hit chain is complicated and beyond the purpose of this code.

```
+ virtual unsigned int get_truth_track_id() const {return UINT_MAX;}  
+ virtual void set_truth_track_id(unsigned int truthTrackId) {}
```

Relatively standalone tracking module, *PHG4TrackFastSim*:

- simulation/g4hough
- Took *PHG4TruthInfoContainer* and *PHG4HitsContainer* as input
- Output *SvtxTrackMap* with *SvtxTrack\_FastSim* filled in.




# Switches

```
PHG4TrackFastSim* kalman = new PHG4TrackFastSim("PHG4TrackFastSim");
kalman->Verbosity(0);
kalman->set_use_vertex_in_fitting(true);
kalman->set_detector_type(PHG4TrackFastSim::Vertical_Plane); // Vertical_Plane, Cylinder
kalman->set_phi_resolution(50E-4);
kalman->set_r_resolution(1.);
kalman->set_mag_field_file_name("fieldmap.root");
kalman->set_mag_field_re_scaling_factor(1.);
kalman->set_pat_rec_hit_finding_eff(1.);
kalman->set_pat_rec_nosise_prob(0.);
kalman->set_do_evt_display(false);

std::string phg4hits_names[] = {"G4HIT_FGEM_0", "G4HIT_FGEM_1", "G4HIT_FGEM_2", "G4HIT_FGEM_3", "G4HIT_FGEM_4"};
kalman->set_phg4hits_names(phg4hits_names, 5);
kalman->set_sub_top_node_name("SVTX");
kalman->set_trackmap_out_name("SvtxTrackMap");
```

# Comparing with previous standalone code

## Standalone program



## This module

